

MIN 2500~6000 TL-X



Most up-to-date smart grid-tied inverter for single phase residential application. innovative aerial material cover, elegant looking and 45% lighter. the OLED screen and touch button design brings more convenient operation. leading high efficiency ensures high energy yields of a home system .

- Maximum efficiency 98.4%
- Dual MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display



GROWATT · PRODUCT

| Datasheet | MIN 2500TL-X | MIN 3000TL-X | MIN 3600TL-X | MIN 4200TL-X | MIN 4600TL-X | MIN 5000TL-X | MIN 6000TL-X |
|---|--|--------------|--------------|--|--------------|--------------|--------------|
| Input Data (DC) | | | | | | | |
| Max. recommended PV power (for module STC) | 3500W | 4200W | 5040W | 5880W | 6440W | 7000W | 8100W |
| Max. DC voltage | 500V | 500V | 550V | 550V | 550V | 550V | 550V |
| Start voltage | | | | 100V | | | |
| Nominal voltage | | | | 360V | | | |
| MPP voltage range | 80V-500V | 80V-500V | 80V-550V | 80V-550V | 80V-550V | 80V-550V | 80V-550V |
| No. of MPP trackers | | | | 2 | | | |
| No. of PV strings per MPP tracker | | | | 1 | | | |
| Max. input current per MPP tracker | | | | 12.5A | | | |
| Max. short-circuit current per MPP tracker | | | | 16A | | | |
| Output data(AC) | | | | | | | |
| AC nominal power | 2500W | 3000W | 600W | 4200W | 4600W | 5000W | 6000W |
| Max. AC apparent power | 2500VA | 3000VA | 3600VA | 4200VA | 4600VA | 5000VA | 6000VA |
| Nominal AC voltage (range*) | Default:240V split-phase, optional:208V & 240V single phase , 183-228@208V 211-264V@240V | | | | | | |
| AC grid frequency (range*) | 50/60 Hz (45-55Hz/55-65 Hz) | | | | | | |
| Max. output current | 11.3A | 13.6A | 16A | 19A | 20.9A | 22.7A | 27.2A |
| Adjustable power factor | 0.8leading...0.8lagging | | | | | | |
| THDi | <3% | | | | | | |
| AC grid connection type | Single phase | | | | | | |
| Efficiency | | | | | | | |
| Max. efficiency | 98.2% | 98.2% | 98.2% | 98.4% | 98.4% | 98.4% | 98.4% |
| European efficiency | 97.1% | 97.1% | 97.2% | 97.5% | 97.5% | 97.5% | 97.5% |
| MPPT efficiency | 99.9% | | | | | | |
| Protection Devices | | | | | | | |
| DC reverse polarity protection | | | | yes | | | |
| DC switch | | | | yes | | | |
| AC/DC surge protection | | | | Type II / Type III | | | |
| Insulation resistance monitoring | | | | yes | | | |
| AC short-circuit protection | | | | yes | | | |
| Ground fault monitoring | | | | yes | | | |
| Grid monitoring | | | | yes | | | |
| Anti-islanding protection | | | | yes | | | |
| Residual-current monitoring unit | | | | yes | | | |
| AFCI protection | | | | yes | | | |
| General Data | | | | | | | |
| Dimensions (W / H / D) | | | | 375/350/160mm | | | |
| Weight | | | | 10.8kg | | | |
| Operating temperature range | | | | -25°C ... +60°C | | | |
| Noise emission (typical) | | | | ≤35 dB(A) | | | |
| Nighttime power consumption | | | | < 1W | | | |
| Topology | | | | Transformerless | | | |
| Cooling | | | | Natural convection | | | |
| Protection degree | | | | IP65 | | | |
| Relative humidity | | | | 0-100% | | | |
| Altitude | | | | 4000m | | | |
| DC connection | | | | H4/MC4(Optional) | | | |
| AC connection | | | | Connector | | | |
| Display | | | | OLED+LED/WIFI+APP | | | |
| Interfaces: RS485 / USB/WI-FI/ GPRS/ RF/LAN | | | | Yes/Yes/Optional/Optional/Optional /Optional | | | |
| Warranty: 5 years / 10 years | | | | Yes /Optional | | | |

CE, IEC62109, G98, G99, VDE0126-1-1, AS4777, AS/NZS 3100, VDE-AR-N4105, CQC, IEC61683, IEC60068, IEC61727, IEC62116, INMETRO, UL1741, UL1741 SA, UL1998, IEEET1547